



2000 Series Male Thread Unions

MTU-2-0325

Spears® Manufacturing Company continues to expand our ever-increasing selection of fitting components. The 2000 Series PVC & CPVC male threaded Union fittings offer more flexibility and space-saving benefits when installing in compact areas.

Typical Usage: Unions offer an integrally-molded male thread eliminating additional cemented or threaded transition joints, allowing for a more compact footprint. Ideal for OEM, skid system manufacturers etc., in applications where space is at a premium.

Many Options Available

- Material: PVC or CPVC
- O-rings: EPDM or FKM
- Sizes: 1/2"-3" (2-1/2" Not Available) & 1-1/4" X 1 Reducing.
- Connections: MPT X Socket & MPT X FPT.
- Pressure Rating: 1/2"-3" 235 psi; Max Internal Pressure Rating @ 73°F (23°C).

2000 Series Male Thread Union Fittings

PVC Fittings



8093-XXX Union 2000
Fipt/Mipt/EPDM O-ring Seal

8053-XXX Union 2000
Fipt/Mipt/FKM O-ring Seal

CPVC Fittings



8093-XXXC Union 2000
Fipt/Mipt/EPDM O-ring Seal

8053-XXXC Union 2000
Fipt/Mipt/FKM O-ring Seal



8094-XXX Union 2000
Socket/Mipt/EPDM O-ring Seal

8054-XXX Union 2000
Socket/Mipt/FKM O-ring Seal



8094-XXXC Union 2000
Socket/Mipt/EPDM O-ring Seal

8054-XXXC Union 2000
Socket/Mipt/FKM O-ring Seal

Size Code	1/2	3/4	1	1-1/4	1-1/2	2	3
XXX	005	007	010	012	015	020	030
Reducing Union (1-1/4X1) = 168							

PROGRESSIVE PRODUCTS FROM SPEARS® INNOVATION & TECHNOLOGY



SPEARS® MANUFACTURING COMPANY
15853 Olden St., Sylmar, CA 91342 • PO Box 9203, Sylmar, CA 91392
(818) 364-1611 • www.spearsmf.com

